40W AC-DC Single Output Desktop SPU41 Type

- Full range AC input
- 3 pole AC inlet IEC320-C14
- Full output 5~40V safety approval
- Compact size, light weight
- Short circuit/ over voltage protection
- LED indicate for power on
- 100% full load burn-in test
- DC output plug option
- Fully enclosed plastic case
- Approvals: UL/ CUL/ TUV/ CE
- OEM brand acceptable
- 1 year warranty

146× 76× 44 mm

AC input range.....90~264VAC/ 1.0A
Inrush current.....cold start, <60A peak@230VAC
Hold up time.....16ms@full load, nominal line
Over load protection.....pulsing mode, auto recovery
Over voltage protection.....110%~145%
Operating temperature.....0~40℃@100% load
Withstand voltage.....I/P-O/P:3KVAC, I/P-FG:1.5KVAC, 1min.
Safety standards.....UL 1950, CSA 22.2, TUV EN60950
EMC standards.....EN55022, IEC801-2,3,4
Humidity.....20%~90%RH
Length of output cable.....180cm for 10~36V; 120cm for +5V
Standard plug of DC output.....2.1φ× 5.5φ× 11mm, center "+"
DIN 5 pin for +5V output

Stock No	Type No	Output	Tol.	R&N	Eff.	P.P.
13071	SPU41-1	5V, 6.00A	5%	50mV	70%	57
13072	SPU41-2	10V, 3.80A	5%	80mV	72%	55
13073	SPU41-3	12V, 3.33A	3%	100mV	74%	55
13074	SPU41-4	15V, 2.66A	3%	120mV	75%	55
13075	SPU41-5	18V, 2.22A	3%	120mV	75%	55
13076	SPU41-6	24V, 1.66A	3%	150mV	78%	55